



DIMENSIONS SHOWN ARE FOR INSTALLATION REFERENCES ONLY AND WILL HAVE TOLERANCE ± 3 mm UNLESS OTHERWISE SPECIFIED

GENERAL:

This floodlight luminaire comprises of die cast Aluminum housing powder coated and toughen glass. This luminaire is recommended for illuminating area lighting, monument lighting, retail shops etc.

PRODUCT DESCRIPTION	**NOMINAL WATTAGE (W)	CCT (K)	CRI	VOLTAGE (V)	**MAINS CURRENT (A)	*APPROX WT (KG)
LDFLX30CDL	30	6500K	>70	230	0.152	0.840

*ONLY FOR STRUCTURAL/MOUNTING DESIGN CONSIDERATION

**RATED SYSTEM WATTAGE AND CURRENT WILL HAVE TOLERANCE AS PER IS 16104: 2012

TITLE: 30W FLOOD LIGHT	TYPE: FLOOD LIGHT	CUSTOMER REFERENCE: --	STAMP: (Controlled Copy) Approved
PREPARED BY Vishal Pawar	CHECKED BY Ramesh.unhavane	APPROVED BY Ramesh.unhavane	

- Note: 1 AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLIED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN
2. THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON GREAVES CONSUMER ELECTRICALS LTD. AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION IN WRITING
3. THE "APPROVED" INDICATED THAT IT IS A CONTROL COPY
4. DIMENSION SHOWN ARE FOR INSTALLATION REFERENCE ONLY AND IN MM WITH TOLERANCE OF ± 3 mm UNLESS OTHERWISE SPECIFIED



Crompton Greaves Consumer
Electricals Ltd.

TECHNICAL DATA SHEET

FORM No. DSG/FR/08

Doc Classification:
Restricted-4

Division:
Lighting

Department: Design
and Development

Document Number: TD 0909251

Revision: R01

Date: 20/07/2023

Page 2 of 3

Issue No. 1

Issue Date:02-05-2018

MATERIAL SPECIFICATIONS:

HOUSING	ALUMINIUM PRESSURE DIE CASTING, BLACK MET TEXTURE RAL 9005 (NEARBY)
FRAME	ALUMINIUM PRESSURE DIE CASTING, BLACK MET TEXTURE RAL 9005 (NEARBY)
GLASS	Toughened Glass
INTERNAL WIRE	PVC coated multistrand wire.
CABLE	3 core PVC coated multistrand cable.
CRADLE	BLACK MET TEXTURE RAL 9005 (NEARBY)

ELECTRICAL PARAMETERS:

Rated Voltage (V)	220 ~240
Frequency (Hz)	50
Operating Voltage Range (V)	140-270
Current (A) @ 240V	0.152mA
Wattage (W) @240V	30W
P.F.	≥0.9
I THD	<20%
Surge	4kV
High Voltage sustain	440Vac @2hrs
Lumen	Rated: 3000-CDL

TITLE: 30W FLOOD LIGHT	TYPE: FLOOD LIGHT	CUSTOMER REFERENCE: --	STAMP: (Controlled Copy) Approved
PREPARED BY Vishal Pawar	CHECKED BY Ramesh.unhavane	APPROVED BY Ramesh.unhavane	

Note: 1 AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLIED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN
 2. THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON GREAVES CONSUMER ELECTRICALS LTD. AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION IN WRITING
 3.THE "APPROVED" INDICATED THAT IT IS A CONTROL COPY
 4. DIMENSION SHOWN ARE FOR INSTALLATION REFERENCE ONLY AND IN MM WITH TOLERANCE OF +/-3mm UNLESS OTHERWISE SPECIFIED



Crompton Greaves Consumer
Electricals Ltd.

TECHNICAL DATA SHEET

FORM No. DSG/FR/08

Doc Classification:
Restricted-4

Division:
Lighting

Department: Design
and Development

Document Number: TD 0909251

Revision: R01

Date: 20/07/2023

Page 3 of 3

Issue No. 1

Issue Date:02-05-2018

INSTALLATION:

Mounting System	Cradle provided for mounting
Mains	Provided 3 CORE; 1 SQMM wire
Protection	IP65

PRODUCT ORDERING CODE:

Product Description	Ordering Code
LDFLX30CDL	LDFLX30CDL

SPARES ORDERING REFERENCE:

Product Description				

TITLE: 30W FLOOD LIGHT	TYPE: FLOOD LIGHT	CUSTOMER REFERENCE: --	STAMP: (Controlled Copy) Approved
PREPARED BY Vishal Pawar	CHECKED BY Ramesh.unhavane	APPROVED BY Ramesh.unhavane	

Note: 1 AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLIED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN
 2. THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON GREAVES CONSUMER ELECTRICALS LTD. AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION IN WRITING
 3.THE "APPROVED" INDICATED THAT IT IS A CONTROL COPY
 4. DIMENSION SHOWN ARE FOR INSTALLATION REFERENCE ONLY AND IN MM WITH TOLERANCE OF +/-3mm UNLESS OTHERWISE SPECIFIED