




Product Name : EXPLORER PC



The product image displayed is for illustration purposes only. The actual product may differ.

Note : Dimension Tolerance is  $\pm 5$ mm and all dimensions are in 'mm'

Description: Flood Light with pressure die cast aluminium housing and Polycarbonate diffuser come lens fixed with silicon gasket and SS screws provides uniform light distribution. Flood light is with Grey powder coated finish for better aesthetics. Mounting bracket provided for installation.

Applications: Driveways/ Sports Lighting/ Smaller Yards/ Bill boards etc.

Housing	Pressure die cast aluminium Poly
Diffuser	carbonate diffuser come lens
Gasket	Silicon
Control Gear	NA
Ingress Protection	IP 66
Impact Resistance	IK 07

LED Make	Bridgelux/Everstar/Equivalent
CCT	5700K $\pm$ 455K
CRI	>80
Luminaire Operating temperature	-10° to +50°
Luminaire Efficacy	100 lm/watt

Rated Voltage and Frequency	240V 50Hz
Safe Operating Voltage Range	140V - 280V AC
Input Wattage	200W
Max Input Current	0.875A
Power Factor	$\geq 0.95$
Protection	High Voltage (440V AC for 2 Hrs.)
Surge Protection	4 kV(Differential Mode)

Sr.no	Product code	Description	Case lot	Weight Approx
1	LPL0200FL0050002	LEDDFL200I5-01PC	2	1.30 Kg

Prepared By: Siddhesh Dalvi Approved by: Rajesh Nair Date: 01/08/2025



Note: \*As per standard, wattage tolerance is  $\pm 10\%$  & Luminaire efficacy tolerance is  $\pm 5\%$  \*Data subject to variation due to change/improvement in the design, materials and process. \*Hardware for installation like bolt and washers are not in Eveready scope

**EVEREADY** **INDUSTRIES INDIA LTD.**

EVEREADY INDUSTRIES INDIA LTD  
2, Rainey Park, Kolkata - 700019  
Email: contactus@eveready.co.in