



Highbays

For high-ceiling applications, Crompton LED Highbays provide reliable, high-performance lighting. Designed to withstand challenging environments, they offer exceptional brightness and longevity, ensuring optimal visibility and operational efficiency.

-  **Best-in-class efficiency**
-  **IP66 ingress protection**
-  **Up to 10kV surge protection**
-  **Additional safety chain**

DELPHINUS

DELPHINUS is a next-generation, energy-saving LED highbay with a pressure die-cast housing, integrated PC optics, and up to 150 lm/W efficacy. It features IP66 ingress protection, IK08 impact resistivity, a safety chain, and surge protection (5 kV in-built). Suitable for surface and suspended mounting.



CAT. REF.	WATTAGE	CASE LOT	MRP(₹)
TIP-323-80-57-60D-HL2-NS-LM-NSG	80	8	13000
TIP-323-80-57-60D-HL3-NS-LM-NSG	80	8	13500
TIP-323-80-57-60D-HL5-NS-LM-NSG	80	8	14600
TIP-324-100-57-60D-HL2-NS-LM-NSG	100	4	14000
TIP-324-100-57-60D-HL3-NS-LM-NSG	100	4	14500
TIP-324-100-57-60D-HL5-NS-LM-NSG	100	4	15700
TIP-328-120-57-60D-HL2-NS-LM-NSG	120	2	15000
TIP-328-120-57-60D-HL3-NS-LM-NSG	120	2	15600
TIP-328-120-57-60D-HL5-NS-LM-NSG	120	2	17000
TIP-329-150-57-60D-HL2-NS-LM-NSG	150	2	18000
TIP-329-150-57-60D-HL3-NS-LM-NSG	150	2	18800
TIP-329-150-57-60D-HL5-NS-LM-NSG	150	2	20000
TIP-332-180-57-60D-HL2-NS-LM-NSG	180	2	22400
TIP-332-180-57-60D-HL3-NS-LM-NSG	180	2	23600
TIP-332-180-57-60D-HL5-NS-LM-NSG	180	2	25000
TIP-332-200-57-60D-HL2-NS-LM-NSG	200	2	23300
TIP-332-200-57-60D-HL3-NS-LM-NSG	200	2	24500
TIP-332-200-57-60D-HL5-NS-LM-NSG	200	2	26000

* Available in different CCT / beam angles

AQUILLA

AQUILLA is a highbay luminaire with a pressure die-cast housing, integrated PC optics, and up to 150 lm/W system efficacy. It features IP66 ingress protection, IK08 impact resistivity, a safety chain, and surge protection (5 kV in-built, 10 kV external). Designed for energy efficiency and durability, it supports surface and suspended mounting.



CAT. REF.	WATTAGE	CASE LOT	MRP(₹)
CIP-323-80-57-60D-HL2-LM-NGG	80	8	15000
CIP-323-80-57-60D-HL3-LM-NGG	80	8	15600
CIP-323-80-57-60D-HL5-LM-NGG	80	8	16400
CIP-324-100-57-60D-HL2-LM-NGG	100	4	16000
CIP-324-100-57-60D-HL3-LM-NGG	100	4	16500
CIP-324-100-57-60D-HL5-LM-NGG	100	4	17800
CIP-328-120-57-60D-HL2-LM-NGG	120	2	17000
CIP-328-120-57-60D-HL3-LM-NGG	120	2	17700
CIP-328-120-57-60D-HL5-LM-NGG	120	2	20000
CIP-329-150-57-60D-HL2-LM-NGG	150	2	20000
CIP-329-150-57-60D-HL3-LM-NGG	150	2	21200
CIP-329-150-57-60D-HL5-LM-NGG	150	2	23000
CIP-329-180-57-60D-HL2-LM-NGG	180	2	26200
CIP-329-180-57-60D-HL3-LM-NGG	180	2	27500
CIP-329-180-57-60D-HL5-LM-NGG	180	2	29000
CIP-329-200-57-60D-HL2-LM-NGG	200	2	27000
CIP-329-200-57-60D-HL3-LM-NGG	200	2	28300
CIP-329-200-57-60D-HL5-LM-NGG	200	2	30000
CIP-326-250-57-60D-HL2-LM-NGG	250	1	30000
CIP-326-250-57-60D-HL3-LM-NGG	250	1	32000

* Available in different CCT / beam angles

CAPRICORNUS

CAPRICORNUS is Toughened glass round highbay in PDC housing suitable for industrial applications. The luminaire has 130 Lm/W efficacy along with IK08 impact resistivity. It has 5kV inbuilt surge protection & ingress protection of IP66 with additional safety chain.

CAT. REF.	WATTAGE	CASE LOT	MRP(₹)
TIP-334-80-57-60D-HL3-NS-GL-NSG	80	4	13650
TIP-334-100-57-60D-HL3-NS-GL-NSG	100	4	14655
TIP-335-120-57-60D-HL3-NS-GL-NSG	120	2	15760
TIP-335-150-57-60D-HL3-NS-GL-NSG	150	2	19000
TIP-336-180-57-60D-HL3-NS-GL-NSG	180	1	23790
TIP-336-200-57-60D-HL3-NS-GL-NSG	200	1	24665

* Available in different CCT / beam angles

ERIDANUS

This Linear Highbay made of premium grade Aluminum extrusion housing with vandal proof polycarbonate lens having superior system efficacy >130 Lm/W & 4kV inbuilt surge protection. Its single point mounting mechanism along with IK10 impact resistivity makes it an ideal choice for Auto ancillary, Food & Beverage industry, warehouses, manufacturing units, assembly lines & airports.

CAT. REF.	WATTAGE	CASE LOT	MRP(₹)
CIS-337-60-57-60D-HL3-LM-NAE	60	2	15125
CIS-337-80-57-60D-HL3-LM-NAE	80	2	16300
CIS-337-100-57-60D-HL3-LM-NAE	100	2	17555
CIS-337-120-57-60D-HL3-LM-NAE	120	2	20835
CIS-337-150-57-60D-HL3-LM-NAE	150	2	21550
CIS-337-200-57-60D-HL3-LM-NAE	200	2	28590

* Available in different CCT / Beam Angles for design based applications

CAPRICORNUS PRO

CAPRICORNUS PRO is a robust LED highbay luminaire with a pressure die-cast housing, toughened glass, and 145 Lm/W efficacy. It features IP66 ingress protection, IK08 impact resistivity, a safety chain, and surge protection (5 kV in-built, 10KV external). Designed with a specialized heat sink and an energy-efficient driver, it meets diverse industrial requirements.

CAT. REF.	WATTAGE	CASE LOT	MRP(₹)
CIP-334-80-57-60D-HL3-GL-NGG	80	4	16300
CIP-334-100-57-60D-HL3-GL-NGG	100	4	17075
CIP-335-120-57-60D-HL3-GL-NGG	120	2	18425
CIP-335-150-57-60D-HL3-GL-NGG	150	2	21850
CIP-336-180-57-60D-HL3-GL-NGG	180	1	28100
CIP-336-200-57-60D-HL3-GL-NGG	200	1	28975
CIP-336-250-57-60D-HL3-GL-NGG	250	1	32650
CIP-334-80-57-60D-HL4-GL-NGG	80	4	18860
CIP-334-100-57-60D-HL4-GL-NGG	100	4	20470
CIP-335-120-57-60D-HL4-GL-NGG	120	2	23000
CIP-336-150-57-60D-HL4-GL-NGG	150	1	26450
CIP-336-180-57-60D-HL4-GL-NGG	180	1	33350
CIP-336-200-57-60D-HL4-GL-NGG	200	1	34500
CIP-336-250-57-60D-HL4-GL-NGG	250	1	36800

* Available in different CCT / beam angles

SCORPIUS

SCORPIUS, Non integral High Ambient LED Highbay is a robust lighting solution designed to operate in industrial environments with elevated temperatures up to 65°C. Their high temp tolerance, energy efficient & rugged design, anti dust coating, long life span, IP66 rating makes them perfect choice for Power Generation, Metal & Mining, Pulp & Paper, Chemical & Petrochemical, and Oil & Gas Industry.

CAT. REF.	WATTAGE	CASE LOT	MRP(₹)
CIP-333-120-57-60D-HL4-GL-NGG	120	1	31150
CIP-333-150-57-60D-HL4-GL-NGG	150	1	33625
CIP-333-180-57-60D-HL4-GL-NGG	180	1	37650
CIP-333-200-57-60D-HL4-GL-NGG	200	1	38650

* Driver to be placed max 30M away from fixture in normal ambient. Wiring between Fixture & Driver not in CGCEL scope



* Application suitable for Eridanus



* Application suitable for Scorpius